



Claims
with corrections

Claim 1 (Previous claim 1) (Currently amended)

(~~An energetic rotary machine,~~) A **Turbinary** type energetic machine having an exterior housing with a cylindrical cavity in (~~are dynamically set up~~) which two complementary compressive parts are set up dynamically, each having a specific number of sides, being a cylindrical part and a paddle part, these parts realizing compression chambers in complicity, **these parts being of the rotary machine type and forming the Material figure of the machine,** (~~the number of compressions realized per cycle being equal or above the number of sides of the paddle~~) the cylindrical part being set up in a rotary manner inside the cylindrical cavity, the cylindrical part having an annular shape with a circular exterior profile and an interior opening chosen in function of the form of the paddle part, the paddle part being set up in the interior opening of the cylindrical part, these complementary compressive parts being connected between themselves and synchronized by a set of mechanical inductions, one of the compressive parts being connected directly or indirectly to an exit power axle, (~~this machine characterizing itself by the rotation of the cylindrical part around the paddle structure, thus describing a rotary movement, whereas each of the points of the paddle structure realize, for a complete machine cycle, a circular figure, the centers of these circular figures being equidistant between themselves, and located in periphery and at an equal distance of the center of the cylindrical cavity, the paddle structure realizing a circular displacement all while conserving a same orientation for all of its course, thus effecting a movement of rotary translation.~~) **this machine being characterized by the fact that each of the points of the paddle part realizes a figure, said Displacement Figure of the paddle part, of a circular shape, the centers of these circular figures being located in periphery and at equal distance from the center of the cylindrical cavity, the paddle part effecting a circular displacement all while conserving a same orientation for it's whole course, thus performing a rotational translation movement, the cylindrical part turning around the paddle part and thus describing a rotary movement, synchronized with that of the paddle part, this realizing a number of paddle compressions per cycle of the paddle equal to the number of paddle sides, the group of the paddle positions during the compressions forming the Geometric Figure, these compressions being realized successively, this forming the Realization Sequence Figure of the machine's Geometric Figure, the support of the paddle part being assured by a mechanic in which the gear ratios which lead the translational orientation movement realizes a retro rotation of the paddle part on the crank pin of the crankshaft or eccentric supporting it in a ratio of one to one to that of the rotation of the crankshaft or eccentric, and the support of the cylindrical part being assured by a mechanic which induces a rotary movement, in which the dynamic is conform with the realization sequence of the Geometric Form, of the Material Form, and of the Realization Sequence of the Geometric Form.**

Claim 2 (previous claim 2) Currently amended

A rotary type energetic machine having an exterior housing with a cylindrical cavity in which are dynamically set up two complementary compressive parts, each having a specific number of sides, being a cylindrical part and a paddle part, these parts realizing compression chambers in complicity, (~~the number of compressions realized per cycle being equal or superior to the number of sides of the paddle structure~~) the cylindrical part being set up in a rotary manner in the cylindrical cavity, the cylindrical part having an annular shape with a circular exterior profile and an interior opening chosen in function of the shape of the paddle part, the paddle (~~structure~~) part being set up in the interior opening of the cylindrical part, **these parts each having a specific number of sides established according to rules of the art of rotary machines, these parts forming the machine's Material Figure, (these complementary compressive parts being connected between themselves and synchronized by a set of mechanical inductions, one of these compressive parts being directly or indirectly connected to a tree of exit power, this machine characterizing itself by the rotation of the cylindrical part around the paddle structure, thus describing a rotary movement, whereas for each of the points of the paddle structure realized, for a complete cycle of the machine, a geometric figure defined by an N number of successive lobes in which the center of this geometric figure coincides with the center of the cylindrical cavity, and which N is superior to two .) each of these complementary compressive parts being guided by a mechanical induction, these inductions being synchronized by the sharing of a common element, one of the mechanical inductions being connected directly or indirectly to an exit power axle, this machine being characterized by the fact that the set of maximal compression locations for a complete machine cycle realizes a geometric figure said Geometric Figure of the machine, all the points of the paddle part realize a same figure defined by N number of successively realized lobes, N being equal to the number of sides of the Geometric Figure, said Displacement Figure, the realization of the totality of the sides of the Geometric Figure being realized by alternating sides, this forming the Realization Sequence of the Geometric Figure, the length of the radius of the eccentric of the paddle part being defined in function of the Material Forms of the machine, and the orientationnel control mechanic of the paddle part being defined according to ratios established according to the relation of the paddle part and the Realization Sequence of the Geometric Figure, the cylindrical part turning around the paddle part thus describing a rotary movement in which the dynamic is conform with the realization sequence of the Geometric Form.**

Claim 3 (New)

A machine as described in 2 in which the figures realized by the Displacement Figure, by the Geometric Figure and by the Geometric Figure Sequence are similar or identical, this figure realizing a number of sides equal to the number of cylinder sides of the opposite rotary type as the machine's Material Figure's cylinder, the center of this geometric figure coinciding with the center of the cylindrical cavity.

Claim 4 New

A machine as described in 2 in which the number of sides of the Geometric Figure is superior or inferior to the number of sides of the opposite cylinder type of that of the Material figure's cylinder, the center of this Geometric Figure coinciding with the center of the cylindrical cavity, the Displacement Figure of the points of the paddle points being different for each point, and different from the Geometric Figure and the Material Figure, the Realization Sequence of the Geometric Figure being successive, and the Realization sequence of the Displacement Figure being done by jumps, the totality of the Displacement Figure being realized in one turn or more of the machine's eccentric, the gear ratios of the induction mechanic of the paddle part being conform with the realization of the Geometric Figure.

Claim 5 (Previous claim5) Currently amended

A machine according to claim 2 and 3, in which the ratio between the retro rotation speed of the paddle structure and the rotation speed of its eccentric is located between $1/X$, where X is the number of sides of the paddle part, and $1/1$.

Claim 6 (Previous claim 6) Currently amended

A machine (~~according to claim 2, in which the geometric figure has N lobes described by the paddle part is produced by successively realizing the sides of this figure.~~) as defined in 3 in which each of the points of the paddle part realizes a similar form of geometric figure, but in which the orientation is different, the realization sequence of the compression locations relative to these lobes being successive and the mechanical induction allowing the orientation control of the paddle part being established according to ratios putting in relation the paddle part and the Geometric figure realization.

Claim 7 (Previous claim 7) Currently amended

A machine (~~according to claim 2, which the order of compressions of a cycle is produced by displacing the paddle part according to the geometric figure by realizing its lobes non successively, the totality of the lobes of this figure being realized by more than a rotation of the paddle part.~~) as defined in 3 in which the realization sequence of the maximal extension locations relative to the lobes is alternative, the realization of the complete machine cycle being realized in more than a machine rotation and the mechanical induction allowing the orientationnel control of the paddle part being established according to ratios putting in relation the paddle part and the realization sequence figure of the geometric figure

Claim 8 (Previous claim 3) Currently amended

A machine according to claim 2, in which a part of the mechanical induction allows the realization of a positioning of the paddle part is defined in function with the compressive parts, and in which the **ratios** mechanical induction part allows the control of the orientation of the paddle part is defined in function with the Geometric figure and Sequential Figures, **in witch the mechanical type of induction preferably stay the same than the type of the Material Figures, or stay near of the one of the 1 one 1 of the translational kinetic**

Claim 8 (Previous claim 19) Currently amended

A machine according to claim (~~1 et 2~~) **4** in which the **orientationnel guiding mechanic of the compressive parts is realized in a semi transmittive manner**, the support gear of the mechanical induction of one of its compressive parts being dynamic.

Claim 9 (Previous claim 17)

A machine according to claim 3 in which the paddle part and the eccentric supporting it all turn in opposite direction of that of the cylinder during an exterior observation.

Claim 10 New

A machine as defined in 1 in which the paddle part is supported by a set of crankshafts set up in a rotary manner inside the machine block, these crankshafts being provided with mechanisms assuring their rotation in the same direction and at the same speed, the crank pin of these crankshafts being inserted in a rotary manner inside one of the piston parts, each of these crankshafts being provided with a gear, each of these gears being coupled to the cylinder induction gear, fixed rigidly to its center.

Claim 11 (Previous claim 22) Currently amended

A machine according to claim 1, 2, or 3, in which the mechanical inductions of the compressive parts (~~share~~) **are exactly synchronized by the sharing of a common element**, this element being either:

- an eccentric,
- a dynamic support gear of a planetary induction, or
- a paddle

Claim 12 (Previous claim 4) Currently amended

A machine according to claim 1 in which the support of the paddle part is assured by a central eccentric, the paddle part having an organizational retro rotation speed equal to the rotation speed of the eccentric, this paddle part being coupled to the cylindrical part.

Claim 13 (Previous claim 5) Currently amended

A machine according to claim (2)4 in which the ratio between the retro rotation speed of the paddle part and the rotation speed of it's eccentric being located between (~~1/X, where X is the number of sides of the paddle part, and 1/1~~) **X/Y**, where **X is the number of paddle sides, and Y being the number of cylinder sides, and X/Z, Z being the number of sides of the anti-rotary figure of the cylinder corresponding to the same paddle.**

Claim 14 (Previous claim 8 an 9 mixed) Currently amended

A machine according to claim 1 in which the dynamic of the compressive parts is realized inversely, the cylindrical part realizing the (~~movement of rotational translation~~) **translational movement or geometric figure** and the paddle part realizing the rotational movement.

Claim 15 (Previous claim 10) original

A machine according to claim 1 or 2, in which the number of sides of the paddle part is superior by one to that of the cylindrical part, the relative number of sides thus realizing the machine in its post rotary form.

Claim 16 (Previous claim 11) original

A machine according to claim 1 or 2 in which the number of sides of the paddle part is inferior by one to that of the cylindrical part, these relative numbers of sides thus realizing the machine in its retro rotary form.

Claim 17 (Previous claim 12) Currently amended

A machine according to claim 1 or 2 in which the paddle part is realized by a plurality of paddle parts, **each of these parts simultaneously realizing the geometric form**, each of these parts, as well as the cylinder, possessing its own mechanical induction, and each of these parts acting in complicity and in synchronization with the cylindrical part.

Claim 18 (Previous claim 13) Currently amended

A machine according to claim 1, 2, or 3, in which the paddle part is constituted of a group of straight segments, connected non-rigidly between each other by their extremities in such manner as to form a flexible paddle structure, called paddle structure, this structure (~~being realized dynamically inside the cylindrical part.~~) **being activated dynamically inside the cylindrical part, the points of this structure realizing the geometric form**

Claim 19 (Previous claim 14) Currently amended

A machine according to claim (~~13~~) 19 in which the movement of **the points of the paddle structure realizes a rectilinear alternative geometric figure.**

Claim 20 (Previous claim 15) Currently amended

A machine according to claim 1, 2, or 3 realized when the support of one of the compressive parts is activated with a mechanical group comprised of a supplementary induction realized in combination with the original induction, (~~making the rotary movement of a compressive part pass to a planetary movement, or even making the simple planetary movement of a compressive part to a composed planetary movement~~) **changing the rotational or planetary movement of this compressive part to a second degree planetary movement, this realizing a second degree geometric figure and an exacerbated material cylinder figure.**

Claim 21 (Previous claim 16) Currently amended

A machine according to claim (1) 2 or 3, (~~putting in~~) **which puts into** layered composition, many (~~groups~~) **sets of compressive parts, the cylindrical part of one of (~~them which could be used~~) these sets being able to serve**, by it's exterior surface, as a paddle part to the exterior compressive part set, and by it's interior surface, as a cylindrical part to the interior compressive parts, **the interior paddle part realizing a geometric figure.**

Claim 21 (Previous claim 16) Currently amended

A machine according to claim (1) 2 or 3, (~~putting in~~) **which puts into** layered composition, many (~~groups~~) **sets of compressive parts, the cylindrical part of one of (~~them which could be used~~) these sets being able to serve**, by it's exterior surface, as a paddle part to the exterior compressive part set, and by it's interior surface, as a cylindrical part to the interior compressive parts, **the interior paddle part realizing a geometric figure.**

Claim 22 (Previous claim 17) Currently amended

A machine according to claim 1 or (2) 3, in which the compressive parts **and their respective mechanical parts** have opposite direction **dynamics** when they're observed from the exterior.

Claim 23 (Previous claim 18) Currently amended

A machine as defined in 1, 2, or 3, in which the movement of one of (~~its~~) the compressive parts is irregular, alternatively realizing accelerations and decelerations which can, when the compressive part possesses a planetary movement, **add an oscillatory character to it, these (~~accelero-decelerative~~) accelerative decelerative movements being able to be realized preferably by means of polycammed gears, these accelerations/decelerations modifying the compressive parts, this modifying, when applied to the cylinder, it's dynamic, and when applied to the compressive part, the original forms of the geometric figure.**

Claim 24 (Previous claim 19) Currently amended

A machine according to claim 1, 2, or 3, in which the mechanical induction support gear of one of the compressive parts is dynamic, **this gear being activated by an induction, said semi transmittive induction .. the geometric figure is obtained by means of a semi transmittive realization.**

Claim 25 New

A machine according to claim 24 in which the rotary part is lead by a semi transmittive induction from center to center, the support and induction axles being both located upon a same center, this semi transmission being either accelerative or decelerative, in either the same or opposite direction.

Claim 26 (Previous claim 20) Currently amended

A machine according to claims 1, 2, or 3, in which the mechanical induction supporting the paddle part is:

a mono induction, an intermediate gear mechanic, a poly induction mechanic, an alternative poly induction mechanic, a hoop gear mechanic, a chained hoop gear mechanic, a double internal gear mechanic, a heel gear mechanic, a gear-like structure mechanic, a unitary gear mechanic, a central active gear mechanic, a stopped poly induction mechanic, a subtractive poly induction mechanic,

these inductions being realized with either with central fixed support gear, with dynamic and central support gear, with peripheral support gear, **these inductions being realized according to gear ratios established in function with the geometric figure or the realization sequence of its faces.**

Claim 28 (Previous claim 21) Currently amended

A machine according to claim 1, 2, or 3 in which the mechanical induction supporting the cylindrical part is one of the following:

a mono induction, an intermediate gear mechanic, a poly induction mechanic, an alternative poly induction mechanic, a hoop gear mechanic, a chained hoop gear mechanic, a double internal gear mechanic, a heel gear mechanic, a gear-like structure mechanic, a unitary gear mechanic, a central active gear mechanic, a stopped poly induction mechanic, a subtractive poly induction mechanic, these inductions being realized with either with central fixed support gear, with dynamic and central support gear, with peripheral support gear, **these mechanical inductions being realized according to gear ratios established in function with the geometric figure or the realization sequence of its faces.**

Claim 29 (Previous claim 23) Currently amended

A machine according to claims 1 or 2 in which the (~~exit tree of~~) power exit shaft is either:

- the (~~tree of the~~) eccentric shaft supporting the compressive paddle part,
- the (~~tree~~)shaft supporting the cylindrical compressive part, or
- **one of the semi transmission axles**

Claim 30 (Previous claim 24) Currently amended

A machine according to claim (2) **31** in which the induction of **either** the cylindrical or the paddle part is said to be descending, this induction **being** characterized (**itself**) by the rigid set-up (~~on~~) **upon** the paddle part of a peripheral support gear, this gear activating indirectly or directly an induction gear, this induction gear being set up rigidly at the center of the cylindrical part of the machine or on an axle of the cylindrical part.

Claim 31 (Previous claim 25)

A machine according to claim 1, 2, or 3, used as : engine, compressor, (~~collection machine~~) , pump, propeller, turbine, mechanical part of a mechanical turbine, artificial heart., **and in with the cycles are definite in relation to the Sequential and the Geometrical figures.**

Claim 32 (Previous claim 26)

A machine according to claims 1 or 2 in which we confer to the paddle part an aerodynamic curve allowing the transportation of substances in the machine:

- from the periphery towards the center
- from the center towards the periphery
- from one lateral face (~~to~~) **towards the other**

Claim 33 (Previous claim 27) Currently amended

A machine according to claims 1, 2, or 3 in which the valves and the spark plugs are installed on the rotary part or the paddle part.

Claim 34 (Previous claim 28) Currently amended

A machine according to claim 1 or 2, in which the locations of emplacements the valves, spark plugs and other accessories are set up in function of the material figure , and **respecting the realization sequence of the compression in coordination with the realization sequence of the Geometrical figure , or of the sequence of realization of the Geometrical figure .**

Claim 35 New

A machine according to claims 1, 2, or 3, in which the direction of the expansion is realized in a straight line, or in a curve in which the general tendency is perpendicular to the line of the piston surface during the explosion.